


**Agilent**  
**82351A PCIe® GPIB Interface Card**

**Data Sheet**



**Agilent Technologies**

## Key Features

- **Compact half-height size (68.9 mm)**
- **High transfer rate of 1.4 MB/s**
- **High flexibility via up-plugging (to x4 or x8 PCIe<sup>®</sup> slots)**
- **3.3 V signal level for lower power consumption**
- **Compatibility with industry standard PCIe<sup>®</sup> rev 1.0a and IEEE-488**
- **Interface to 14 GPIB instruments (max)**

## Recommended use

- **Bandwidth-intensive test applications**
- **Adding GPIB connection for PCIe<sup>®</sup>-based PCs or workstations**

## High transfer rate for demanding test applications

Agilent 82351A PCIe<sup>®</sup>-GPIB interface card is designed for integration into next generation PCs or workstations. It offers fast data transmission for various demanding test applications that require data to be transferred to memory fast enough without any lost or overwritten.

PCIe<sup>®</sup> (PCI Express<sup>®</sup>) is an evolutionary version of PCI that offers a higher transfer rate across a low number of wires. It is also backward-compatible with PCI software, so you don't need to perform any code re-configuration.

PCIe<sup>®</sup>'s powerful bus architecture allows bi-directional data transmission, and the implementation of a new class of test applications.

## 82351A Technical Specifications

### General requirements

Minimum system requirements	Windows <sup>®</sup> 2000/XP
Software required	Agilent IO Libraries Suite 14.2 and above, with the following requirements: <ul style="list-style-type: none"><li>• Windows<sup>®</sup> XP Pro or Home edition service pack 1 or later</li><li>• Windows<sup>®</sup> 2000 Pro service pack 4 or later and Microsoft Internet Explorer 5.01 or greater</li><li>• 450 MHz Intel Pentium<sup>®</sup> processor and 800x600 display with 256 colors</li><li>• 128 megabytes RAM and 225 MB total hard disk space</li><li>• Supported APIs include Agilent or NI VISA, SICL, VISA-COM and NI-488.2</li></ul>
PCI bus slot	3.3 V PCIe <sup>®</sup> slot, 32 bits
Supported standards	PCIe <sup>®</sup> rev. 1.0a IEEE 488.1 and IEEE 488.2 compatible

### General characteristics

Power	Backplane +3.3 V PCIe <sup>®</sup>
Connectors	Standard 24-pin (IEEE-488)  +1.5 V PCIe <sup>®</sup>
Maximum data rate	1.4 MB/s or better
Maximum instrument connection	14 instruments—daisy chain via GPIB
Buffering	Built-in
Configuration	Plug-and-Play
EMC and safety *	IEC 61010-1:2001 / EN61010-1:2001 IEC 61326:2002/EN61326:1997+A1:1998+A2:2001+A3:2003 Pollution Degree 2 This product is rated for indoor use only
Warranty	1 year

### Dimensions

Width, depth and height	158.0 mm (W) x 120.8 mm (D) x 21.6 mm (H)
Weight	0.082 kg

### Environmental specifications

Operating environment	–5 °C to 60 °C
Operating humidity	Up to 90% at 40 °C non-condensing
Storage environment	–40 °C to 70 °C
Storage humidity	Up to 90% at 65 °C non-condensing

\* **Additional detail and information in the Declaration of Conformity**



### Agilent Email Updates

[www.agilent.com/find/emailupdates](http://www.agilent.com/find/emailupdates)

Get the latest information on the products and applications you select.



[www.axistandard.org](http://www.axistandard.org) AdvancedTCA® Extensions for Instrumentation and Test (AXIe) is an open standard that extends the AdvancedTCA® for general purpose and semiconductor test. Agilent is a founding member of the AXIe consortium.



[www.lxistandard.org](http://www.lxistandard.org)

LAN eXtensions for Instruments puts the power of Ethernet and the Web inside your test systems. Agilent is a founding member of the LXI consortium.



<http://www.pxisa.org>

PCI eXtensions for Instrumentation (PXI) modular instrumentation delivers a rugged, PC-based high-performance measurement and automation system.

### Agilent Channel Partners

[www.agilent.com/find/channelpartners](http://www.agilent.com/find/channelpartners)

Get the best of both worlds: Agilent's measurement expertise and product breadth, combined with channel partner convenience.

Windows is U.S. registered trademarks of Microsoft Corporation.

PCIe® and the PCI Express® are US registered trademarks and/or service marks of PCI-SIG.



Agilent Advantage Services is committed to your success throughout your equipment's lifetime. We share measurement and service expertise to help you create the products that change our world. To keep you competitive, we continually invest in tools and processes that speed up calibration and repair, reduce your cost of ownership, and move us ahead of your development curve.

[www.agilent.com/find/advantageservices](http://www.agilent.com/find/advantageservices)



[www.agilent.com/quality](http://www.agilent.com/quality)

For more information on Agilent Technologies' products, applications or services, please contact your local Agilent office. The complete list is available at:

[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)

### Americas

Canada	(877) 894 4414
Brazil	(11) 4197 3500
Mexico	01800 5064 800
United States	(800) 829 4444

### Asia Pacific

Australia	1 800 629 485
China	800 810 0189
Hong Kong	800 938 693
India	1 800 112 929
Japan	0120 (421) 345
Korea	080 769 0800
Malaysia	1 800 888 848
Singapore	1 800 375 8100
Taiwan	0800 047 866
Other AP Countries	(65) 375 8100

### Europe & Middle East

Belgium	32 (0) 2 404 93 40
Denmark	45 70 13 15 15
Finland	358 (0) 10 855 2100
France	0825 010 700*
*0.125 €/minute	
Germany	49 (0) 7031 464 6333
Ireland	1890 924 204
Israel	972-3-9288-504/544
Italy	39 02 92 60 8484
Netherlands	31 (0) 20 547 2111
Spain	34 (91) 631 3300
Sweden	0200-88 22 55
United Kingdom	44 (0) 118 9276201

*For other unlisted Countries:*

[www.agilent.com/find/contactus](http://www.agilent.com/find/contactus)

Revised: October 14, 2010

Product specifications and descriptions in this document subject to change without notice.

© Agilent Technologies, Inc. 2011  
Printed in USA, May 10, 2011  
5989-7049EN



Agilent Technologies